

TEMADUR UV-EXTRA

DESCRIPTION

An additive which improves the resistance against UV light.

PRODUCT FEATURES AND RECOMMENDED USES

- ◆ Improves the weather resistance of TEMADUR paints and varnishes.
- ◆ Suitable for use in TEMADUR products.
- ◆ Gives more protection against UV light and thus improves the gloss and colour retention of the coating.

TECHNICAL DATA

Specific gravity

0.9 kg / l

Product code

990 0897

Directions for use

Mix the base and hardener. Add the TEMADUR UV-EXTRA solution, max. 10 % by volume, and stir thoroughly. If necessary thin with Thinner 1048.

VOC

The Volatile Organic Compounds amount to 760 ± 20 g/l solution.

HEALTH AND SAFETY

Containers are provided with safety labels, which should be observed. Further information about hazardous influences and protection are detailed in individual health and safety data sheets.

A health and safety data sheet is available on request from Tikkurila Coatings Oy.

For professional use only.

The above information, based on laboratory tests and practical experience, has been proved valid at the date marked on the product data sheet. When necessary verify the validity of the product data sheet. The quality of the product is ensured by our operational system, based on the requirements of the standards ISO 9001 and ISO 14001. As a manufacturer we cannot be responsible for any damages caused by using the product against our instructions or for inappropriate purposes.

mko161002/tmk171002/990 0897